Water Wise Gilbert Recommendations Checklist

Equipment	Recommendation	Notes
(Required)		
Faucet Aerators	Install 0.5 gpm aerators on all hand wash faucets. Install 1.0 gpm aerators on kitchen faucets.	Gilbert Water Conservation provides free of charge. Labor assistance available. Exempt faucets are any where aerators are built into the fixture or where sinks are used for filling large containers.
Pre-Rinse Spray Valves	Install 1.1 gpm valves in place of any existing less efficient models.	Gilbert Water Conservation provides free of charge. Labor assistance available.
Showerheads	Install 1.5 gpm showerheads in place of any existing less efficient models.	Gilbert Water Conservation provides free of charge.

gpm = gallons per minute

Practice/Action	Recommendation	Notes
(Required)		
Repair Leaks	Any identified active or intermittent leaks must be repaired within 90 days.	If a leak pertains to old equipment, Gilbert Water Conservation has some funding to assist with purchase of more efficient equipment.
Misting System	Implement customized best management practice for running misters as approved by Water Conservation.	Gilbert Water Conservation can assist with funding automatic timers where water savings opportunities are evident. Submeters also available.
Serve Water Upon Request	Only serve glasses of water to patrons who specifically ask.	Gilbert Water Conservation has table tents or coasters or short menu brief explaining the reasons for this practice to patrons if desired.
Cooling Tower or Evaporative Cooler Efficiency	 Implement specific custom best practices as noted by Gilbert Water Conservation Enroll asset manager and treatment vendor in Gilbert-sponsored platform for tracking. 	Gilbert Water Conservation funding available to assist with water-saving upgrades and sub-meters.

Water Wise Gilbert Recommendations Checklist (Prestigious Partner)

Practice/Action	Recommendation	Notes
(Suggested)		
Urinal Toilet Diaphragms	Replace with 0.5 gpf diaphragms.	Water Conservation can provide free of charge. Note specific urinal china and only replace if within specified recommended range.
Bowl Toilets	Replace or adjust any bowl toilet diaphragms where toilets are flushing longer than 5 seconds	Toilets flushing longer than 4 seconds use more than the stamped gallon flush rate.
Smart Irrigation Controller or Rain Sensor	Replace existing controller with weather- based controller, or add rain sensor to existing standard controller.	Gilbert Water Conservation can provide free of charge. Programming assistance available for optimal watering. Determine if wifi is available for specific model recommendations.
Employee Training	Participate in water conservation employee training session (about 1 hour long)	Sponsored and presented by Gilbert Water Conservation. No special prerequisites from the organization are required.
Employee Volunteer Participation at Gilbert Water Festival	Sign up to volunteer at this annual event that instructs local 4th graders about water, takes place in the Spring in Gilbert.	Sponsored and coordinated by Gilbert Water Conservation. No special prerequisites from the organization are required.

